

# Standard intrinsic module ISO\_C\_BINDING

July 31, 2012

## 1 Name

`iso_c_binding` — standard intrinsic module

## 2 Usage

```
USE,INTRINSIC :: ISO_C_BINDING
```

(The `’,INTRINSIC ::’` part is optional.)

## 3 Synopsis

ISO\_C\_BINDING provides named constants, types and procedures that are useful in a mixed-language (C and Fortran) program.

## 4 Parameter Descriptions

### 4.1 Kind Parameter Values

The following parameters are all KIND values for matching C types to a Fortran type and kind. If a particular C type has no matching Fortran kind, the parameter value will be negative.

```
INTEGER,PARAMETER :: c_int = ...
INTEGER,PARAMETER :: c_short = ...
INTEGER,PARAMETER :: c_long = ...
INTEGER,PARAMETER :: c_long_long = ...
INTEGER,PARAMETER :: c_signed_char = ...
INTEGER,PARAMETER :: c_size_t = ...
INTEGER,PARAMETER :: c_intmax_t = ...
INTEGER,PARAMETER :: c_intptr_t = ...
```

Kind parameter values for the C integral types `int`, `short`, `long`, `long long`, `signed char`, `c_size_t`, `intmax_t` and `c_intptr_t`. These are all kind values for type `INTEGER`.

```
INTEGER,PARAMETER :: c_int8_t = ...
INTEGER,PARAMETER :: c_int16_t = ...
INTEGER,PARAMETER :: c_int32_t = ...
INTEGER,PARAMETER :: c_int64_t = ...
INTEGER,PARAMETER :: c_int_least8_t = ...
INTEGER,PARAMETER :: c_int_least16_t = ...
INTEGER,PARAMETER :: c_int_least32_t = ...
INTEGER,PARAMETER :: c_int_least64_t = ...
INTEGER,PARAMETER :: c_int_fast8_t = ...
```

```

INTEGER,PARAMETER :: c_int_fast16_t = ...
INTEGER,PARAMETER :: c_int_fast32_t = ...
INTEGER,PARAMETER :: c_int_fast64_t = ...

```

Kind parameter values for the C integral types `int8_t` to `int_fast64_t`. These are all kind values for type `INTEGER`.

```

INTEGER,PARAMETER :: c_float = ...
INTEGER,PARAMETER :: c_double = ...
INTEGER,PARAMETER :: c_long_double = ...

```

Kind parameter values for the C floating-point types `float`, `double` and `long double`. These are all kind values for type `REAL`.

```

INTEGER,PARAMETER :: c_float_complex = c_float
INTEGER,PARAMETER :: c_double_complex = c_double
INTEGER,PARAMETER :: c_long_double_complex = c_long_double

```

Kind parameter values for the C `_Complex` family of types. These always have exactly the same values as `c_float` et al, and are included only for unnecessary redundancy.

```

INTEGER,PARAMETER :: c_bool = ...

```

Kind parameter value for the C type `_Bool`, for use with the `LOGICAL` type.

```

INTEGER,PARAMETER :: c_char = ..

```

Kind parameter value for the C type `char`, for use with the `CHARACTER` type.

## 4.2 Character Constants

The following parameters give Fortran values for all of the C “backslash” escape sequences.

```

CHARACTER,PARAMETER :: c_null_char = char(0)           ! C '\0'
CHARACTER,PARAMETER :: c_alert = achar(7)              ! C '\a'
CHARACTER,PARAMETER :: c_backspace = achar(8)          ! C '\b'
CHARACTER,PARAMETER :: c_form_feed = achar(12)         ! C '\f'
CHARACTER,PARAMETER :: c_new_line = achar(10)          ! C '\n'
CHARACTER,PARAMETER :: c_carriage_return = achar(13)   ! C '\r'
CHARACTER,PARAMETER :: c_horizontal_tab = achar(9)      ! C '\t'
CHARACTER,PARAMETER :: c_vertical_tab = achar(11)      ! C '\v'

```

## 4.3 Pointer Constants

```

TYPE(c_ptr),PARAMETER :: c_null_ptr = c_ptr(...)

```

This is a C null pointer, equivalent to `(void *)0` in C.

```

TYPE(c_funptr),PARAMETER :: c_null_funptr = c_funptr(...)

```

This is a C null function pointer.

## 5 Type Definitions

```
TYPE c_funptr
  PRIVATE
  ...
END TYPE
```

This type represents a C function pointer, and is used when passing procedure arguments to a C routine. The interface to the C routine is declared with a `TYPE(c_funptr)` dummy argument, and values of this type can be created by using the function `c_funloc` on a procedure name (see below for restrictions).

```
TYPE c_ptr
  PRIVATE
  ...
END TYPE
```

This type represents a ‘(void \*)’ C data pointer, and is used when passing pointer arguments to a C routine. The interface to the C routine is declared with a `TYPE(c_ptr)` dummy argument; values of this type are created using the `c_loc` function (Fortran) pointer or target (see below for restrictions). A C pointer can be turned into a Fortran pointer using the `c_f_pointer` function (see below for the full description).

## 6 Procedure Descriptions

All the procedures provided are generic and not specific. None of the procedures are pure.

In the descriptions below, `TYPE(*)` means any type (including intrinsic types), and `INTEGER(*)` means any kind of `INTEGER` type.

```
INTERFACE c_associated
  LOGICAL FUNCTION c_associated...(c_ptr1,c_ptr2) ! Specific name not visible
    TYPE(c_ptr),INTENT(IN) :: c_ptr1,c_ptr2
    OPTIONAL c_ptr2
  END
  LOGICAL FUNCTION c_associated...(c_ptr1,c_ptr2) ! Specific name not visible
    TYPE(c_funptr),INTENT(IN):: c_ptr1,c_ptr2
    OPTIONAL c_ptr2
  END
END INTERFACE
```

Returns true if and only if `c_ptr1` is not a null pointer and, if `c_ptr2` is present, the same as `c_ptr2`.

```
INTERFACE c_f_pointer
  SUBROUTINE c_f_pointer...(cptr,fptra) ! Specific name not visible
    TYPE(c_ptr),INTENT(IN) :: cptr
    TYPE(*),INTENT(OUT),POINTER :: fptra
  END
  SUBROUTINE c_f_pointer...(cptr,fptra,shape) ! Specific name not visible
    TYPE(c_ptr),INTENT(IN) :: cptr
    TYPE(*),INTENT(OUT),POINTER :: fptra(...)
```

```

        INTEGER(*),INTENT(IN) :: shape(:)
    END
END INTERFACE

```

Converts a C address to a Fortran pointer. If `fptr` is an array, `shape` must be an array whose size is equal to the rank of `fptr`.

```

INTERFACE c_f_procpointer
    ...
END INTERFACE

```

This procedure is not available in release 5.1. It converts `TYPE(c_funptr)` into Fortran procedure pointers.

```

INTERFACE c_funloc
    TYPE(c_funptr) FUNCTION c_funloc...(x) ! Specific name not visible
    EXTERNAL x
END
END INTERFACE

```

Returns the C address of a Fortran procedure, which must be a dummy procedure, external procedure or module procedure, and must have the `BIND(C)` attribute.

Note that since Fortran procedure pointers are not available in release 5.1, invoking a procedure through a `TYPE(c_funptr)` value can only be done from C.

```

INTERFACE c_loc
    TYPE(c_ptr) FUNCTION c_loc...(x) ! Specific name not visible
    TYPE(*),TARGET :: x
END
END INTERFACE

```

Returns the C address of a Fortran variable, which must have the `TARGET` attribute and must not be polymorphic (i.e. it must not be declared with the `CLASS` keyword). If `x` is a pointer, it must be associated with a target; if `x` is allocatable, it must be allocated with non-zero size. If `x` is an array, it must have interoperable type and type parameters.

## 7 See Also

`nag_modules(3)`.

## 8 Bugs

Please report any bugs found to ‘support@nag.co.uk’ or ‘support@nag.com’, along with any suggestions for improvements.

## 9 Author

Malcolm Cohen, Nihon Numerical Algorithms Group KK, Tokyo, Japan.